



A

Express Mail Label No. EM192722923US
Date of Deposit: September 23, 1997

ATTORNEY'S DOCKET NO. E0295/7021 RFG

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

BOX PATENT APPLICATION
ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, D.C. 20231

Sir:

TRANSMITTED HERewith FOR FILING IS A PATENT APPLICATION OF:

INVENTOR(S) Robert Wilson, Dennis P.J. Ting, Mehamood Hosein

TITLE: A METHOD AND APPARATUS FOR IMPLEMENTING
A REMOTE MIRRORING DATA FACILITY

ENCLOSED ARE:

- [X] FIVE (5) SHEETS OF INFORMAL DRAWINGS (Figs. 1-5)
- [X] A SPECIFICATION, CLAIMS AND ABSTRACT TOTALING 28 PAGES
- [X] AN ASSIGNMENT OF THE INVENTION TO EMC Corporation
- [X] PATENT ASSIGNMENT RECORDATION FORM COVER SHEET (FORM PTO-1595)
- [X] DECLARATION AND POWER OF ATTORNEY (Signed)

CLAIMS AS FILED

FOR	NUMBER FILED		NUMBER EXTRA		RATE	BASIC FEE \$770.00	
TOTAL CLAIMS	61	-	20	=	41 x \$ 22	=	\$902.00
INDEP. CLAIMS	10	-	3	=	7 X \$ 80	=	\$560.00
ASSIGNMENT RECORDING FEE						=	\$ 40.00
TOTAL FILING FEE						=	\$2,272.00

- [X] THE COMMISSIONER IS HEREBY AUTHORIZED TO CHARGE ANY ADDITIONAL FEES WHICH MAY BE REQUIRED, OR CREDIT OVERPAYMENT TO ACCOUNT NO. 23/2825. A DUPLICATE OF THIS SHEET IS ENCLOSED.

[X] A CHECK IN THE AMOUNT OF \$2,272.00 TO COVER THE FILING FEE IS ENCLOSED.



Richard F. Giunta
Reg. No. 36,149
Wolf, Greenfield & Sacks, P.C.
600 Atlantic Avenue
Boston, MA 02210-2211
(617)720-3500
Attorneys of Record

Docket No. E0295/7021 RFG
Date: September 23, 1997

140113.1

**A METHOD AND APPARATUS FOR IMPLEMENTING
A REMOTE MIRRORING DATA FACILITY**

Field of the Invention

5 The present invention is directed to a method and apparatus for implementing an interface between a source storage device and a remotely disposed target mirroring storage device.

Background of the Invention

10 An illustrative configuration of a remote mirroring data facility is shown in Fig. 1. In the system shown in Fig. 1, a host CPU 1 is coupled to a source storage device 3 through a source storage controller 5. The storage device 3 may be a large disc drive providing main storage for the host CPU 1, or it may be a plurality of smaller disc drives arranged to perform the same function. An example of such a storage device is the SYMMETRIX line of disc arrays, available from EMC Corporation, Hopkinton, MA.

15 The data stored in storage device 3 may be crucial to the operation of host CPU 1. Therefore, a contingency solution is desirable in the event that a problem is experienced with the storage device 3, to ensure that the stored data is not lost and to minimize the risk of CPU 1 being down due to problems with the storage device. Potential problems with the storage device 3 can include hardware and software errors that may make stored data unrecoverable, as well as
20 catastrophic events, such as an earthquake or other natural disaster that could result in the destruction of the storage device.

 One solution for protecting the data stored in storage device 3 is to mirror the data in another storage device. Fig. 1 illustrates such a system, wherein the source storage controller 5 is coupled to a target storage controller 7 and an associated target storage device 9. As data is written to the
25 source storage device 3, it can also be written and mirrored to the target storage device 9. If the storage device 3 is destroyed or experiences an error that renders stored data unrecoverable, the data can be retrieved from the mirroring storage device 9. As shown in Fig. 1, the target storage controller 7 and target storage device 9 can also serve as the main storage system for another host CPU 11. Alternatively, the target storage system can be dedicated solely to mirroring the data stored
30 in the source storage system, without being coupled to another CPU.

The level of protection provided by the system shown in Fig. 1 is enhanced when the mirroring target storage system (controller 7 and storage device 9) is disposed at a location remote from the source storage system (controller 5 and storage device 3), so that if a catastrophe occurs that destroys the source system, the likelihood of the mirroring storage system also being destroyed is greatly decreased. Thus, it is advantageous to implement a link 13 between the source and target storage controllers 5 and 7 that enables the target storage system to be disposed a relatively long distance away from the source storage system.

Communication between the host CPU 1 and the source storage controller 5 is typically performed using one of a number of standard protocols, including SCSI, BUS and TAG (B&T), or more typically ESCON. ESCON is a standard computer system interface and protocol developed by International Business Machines (IBM). ESCON defines the interface and protocol for communicating over a link 15 between the host CPU 1 and the source storage controller, and is described in detail, for example, in "ENTERPRISE SYSTEMS ARCHITECTURE/390 - ESCON I/O INTERFACE", 3rd Edition (1992) published by IBM. Because ESCON is used as the protocol to establish the interface between the host CPU 1 and the source storage controller 5, it has also conventionally been used to implement the link 13 between the source and target storage controllers 5 and 7 in a remote mirroring data facility such as the one shown in Fig. 1. Thus, link 13 has conventionally been implemented using a dedicated ESCON link that allows the target storage controller 7 to be disposed at a location somewhat remote from the source storage controller 5. However, these dedicated links have conventionally been limited to relatively short distances. For example, IBM states that its dedicated ESCON links are limited to approximately 60km. Although this number may be conservative, it is believed that conventional dedicated ESCON links are limited to distances of approximately 80km, even when appropriate repeaters are used along the line.

The use of a dedicated ESCON line to implement the link 13 between the source and target storage controllers 5 and 7 in a remote mirroring data facility is disadvantageous for two reasons. First, the above-described limit on the maximum supported distance may be insufficient for some applications. Second, it is often costly to implement these dedicated links because they are not part of a public communications network, and may not be capable of implementation over pre-existing communication lines.

To address the foregoing limitations on the use of a dedicated ESCON link to implement a

remote mirroring data facility, the assignee of the present application has developed a technique for implementing a remote mirroring data facility using a link 13 implemented through pre-existing public communication channels, as disclosed in the following two U.S. patent applications, each of which is incorporated herein by reference: serial no. 08/601,733, entitled METHOD AND

5 APPARATUS FOR INTERFACING TWO REMOTELY DISPOSED DEVICES COUPLED VIA A TRANSMISSION MEDIUM, filed February 15, 1996; and serial no. (not yet assigned), entitled METHOD AND APPARATUS FOR INTERFACING TWO REMOTELY DISPOSED DEVICES COUPLED VIA A TRANSMISSION MEDIUM, filed August 25, 1997 (collectively assignee's co-pending applications).

10 The co-pending applications are directed to the implementation of the link 13 between the source and target storage controllers of a remote mirroring data facility via a data communication line operable in a public communications network. The specific embodiments discussed include data communication lines of the type leased by telephone service companies, such as data communication lines from the family of T-carriers available in North America (e.g., T1, T3 and T5) and the family of CEPT communication links available in Europe (e.g., CEPT-1 and CEPT-3).
15 Leased lines such as a T-3 line are a service provided by telephone service companies in which a subscriber pays a flat fee to lease exclusive use of a data communication link between two locations. These leased lines employ existing telephone lines, satellite links, etc., to provide high speed data transmission within a public communications network between the two points requested by the subscriber. By implementing the link 13 in a remote mirroring data facility through a public
20 communications network, the expense and time that would be incurred in implementing a conventional dedicated ESCON link between the source and target storage controllers 5 and 7 is avoided. Furthermore, the limitation on the distance over which dedicated ESCON links can extend is overcome, enabling the link 13 to be extended for significantly greater distances, thereby
25 providing increased flexibility in implementing a user's desired configuration and providing enhanced protection in the event of a natural disaster or other catastrophe.

In the assignee's co-pending applications, a number of different protocols are specified for communicating between the source and target storage controllers 5 and 7 through the public communications network to achieve performance improvements as compared with the ESCON
30 protocol. The use of a leased line and any one of these protocols achieves a high performance

remote mirroring data facility. However, some user applications may not require the high performance achieved through the use of a leased line, and might desire a more inexpensive solution for implementing the link 13 between the source and target storage controllers in a remote mirroring data facility.

- 5 In view of the foregoing, it is an object of the present invention to provide an inexpensive link between two remotely disposed storage systems in a remote mirroring data facility.

Summary of the Invention

- One illustrative embodiment of the invention is directed to a computer system comprising a
10 central processing unit (CPU); a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system; a second storage system; at least one communication link coupling the second storage system to the CPU, the at least one communication link including a network cloud that is shared with at least one other resource so that no portion of the network cloud is dedicated exclusively to transferring information between the CPU and the second storage system;
15 and a mirroring controller to mirror at least some of the information stored in the first storage system in the second storage system by transferring the at least some of the information through the network cloud.

- Another illustrative embodiment of the invention is directed to a computer system comprising a central processing unit (CPU); a first storage system that is coupled to the CPU so that
20 the CPU can store information in the first storage system; a second storage system; at least one communication link coupling the second storage system to the CPU, the at least one communication link including at least one wireless connection; and a mirroring controller to mirror at least some of the information stored in the first storage system in the second storage system by transferring the at least some of the information over the at least one communication link.

- 25 A further illustrative embodiment of the invention is directed to a computer system comprising a central processing unit (CPU); a first storage system; a first communication link coupling the first storage system to the CPU so that the CPU can store information in the first storage system; a second storage system; a second communication link coupling the second storage system to the CPU; a third storage system; a third communication link coupling the third storage
30 system to the CPU; and a mirroring controller to mirror at least some of the information stored by

the CPU in the first storage system in both the second and third storage systems.

Another illustrative embodiment of the invention is directed to a method of operating a computer system that includes a central processing unit (CPU), a first storage system, a first communication link coupling the first storage system to the CPU so that the CPU can store
5 information in the first storage system, a second storage system, a second communication link coupling the second storage system to the CPU, a third storage system, and a third communication link coupling the third storage system to the CPU. The method comprises a step of (A) mirroring at least some of the information stored by the CPU in the first storage system in both the second and third storage systems by transferring the at least some of the information over the second and third
10 communication links.

A further illustrative embodiment of the invention is directed to a method of mirroring information stored in a computer system comprising a central processing unit (CPU), a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system, and a second storage system coupled to the CPU by at least one communication link, the at least one
15 communication link including a network cloud that is shared with at least one other resource so that no portion of the network cloud is dedicated exclusively to coupling the second storage system to the CPU. The method comprises a step of (A) transmitting at least some of the information stored by the CPU in the first storage system into the network cloud with the second storage system designated as a destination for the at least some of the information, so that the at least some of the
20 information can be transferred through the network cloud and mirrored in the second storage system.

A further illustrative embodiment of the invention is directed to a computer system capable of mirroring information in a remotely disposed target storage system that is coupled to the computer system via at least one communication link that includes a network cloud that is shared
25 with at least one other resource. The computer system comprises a central processing unit (CPU) coupled to the network cloud; a source storage system that is coupled to the CPU so that the CPU can store information in the source storage system; and a controller to transfer at least some of the information stored in the source storage system into the network cloud so that the at least some of the information can be mirrored in the target storage system.

30 Another illustrative embodiment of the invention is directed to a computer system capable of

mirroring information in a remotely disposed target storage system that is coupled to the computer system via at least one communication link that includes at least one wireless connection. The computer system comprises a central processing unit (CPU) coupled to the at least one communication link; a source storage system that is coupled to the CPU so that the CPU can store
5 information in the source storage system; and a controller to transfer at least some of the information stored in the source storage system into the network cloud so that the at least some of the information can be mirrored in the target storage system.

Another illustrative embodiment of the invention is directed to a computer system comprising a central processing unit (CPU); a first storage system that is coupled to the CPU so that
10 the CPU can store information in the first storage system; a second storage system; at least one communication link coupling the second storage system to the CPU so that the CPU can store information in the second storage system, the at least one communication link being selected from one of an Ethernet link, an asynchronous transfer mode (ATM) link, an FDDI link and a fibre channel link; and a mirroring controller to mirror at least some of the information stored in the first
15 storage system in the second storage system by transferring the at least some of the information over the at least one communication link.

A further illustrative embodiment of the invention is directed to a computer system comprising a central processing unit (CPU); a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system; a second storage system; at least one
20 communication link coupling the second storage system to the CPU so that the CPU can store information in the second storage system, the at least one communication link being one of a packet switched network and a cell switched network; and a mirroring controller to mirror at least some of the information stored in the first storage system in the second storage system by transferring the at least some of the information over the at least one communication link.

Another illustrative embodiment of the invention is directed to a computer system comprising a central processing unit (CPU); a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system; a second storage system; at least one
25 communication link coupling the second storage system to the CPU so that the CPU can store information in the second storage system, the at least one communication link including a network cloud; and a mirroring controller to mirror at least some of the information stored in the first storage
30

system in the second storage system by transferring the at least some of the information over the network cloud.

Brief Description of the Drawings

Fig. 1 illustrates a conventional remote mirroring data facility;

Fig. 2 illustrates a remote mirroring data facility implemented using a network cloud in accordance with one illustrative embodiment of the invention;

Fig. 3 schematically represents a number of layers and protocols used in implementing the embodiment of the present invention directed to the use of a network cloud in a remote mirroring data facility;

Fig. 4 illustrates the fragmentation of information via multiple controllers in accordance with one illustrative embodiment of the invention; and

Fig. 5 illustrates a remote mirroring data facility including a wireless communication link between the source and target storage system in accordance with another illustrative embodiment of the invention.

Detailed Description

One aspect of the present invention is directed to a method and apparatus for implementing a link between two remotely disposed storage systems in a remote mirroring data facility over a pre-existing and inexpensive data communication link. In one illustrative embodiment of the invention, a communication network that is accessible by other resources on a multiplexed basis is used to implement the link between the source and target storage controllers 5 and 7 (Fig. 1), such that the remote mirroring data facility does not have exclusive use of any portion of the network. For example, the communication link 13 can be implemented over the Internet. Alternatively, the link 13 can be implemented over an intranet, or any network cloud. As used herein, the term network cloud defines a communication link that implements a protocol wherein information transferred through the cloud includes a destination address so that the information can be transported by the cloud to the appropriate destination. In another illustrative embodiment of the invention, the link 13 is implemented in a completely wireless fashion (e.g., using satellite or microwave point-to-point technology).

A first illustrative embodiment of the present invention is shown in Fig. 2, wherein the link 13 between the source and target storage controllers 5 and 7 is implemented via a network cloud 15. In contrast to a dedicated ESCON link or the use of a dedicated public communications resource (e.g., a T3 line), the network cloud 15 is a resource that typically is shared by the remote mirroring data facility with a number of additional applications 17.

In one illustrative embodiment of the invention, the network cloud 15 is implemented via the Internet. Since most user sites wherein the source and target storage systems are located will have easy access to the Internet, no significant costs will be incurred in implementing the network cloud 15. In addition, the use of the network cloud 15 renders it unnecessary to lease a dedicated public communication line to interconnect the source and target storage systems, resulting in a less expensive implementation of the remote mirroring data facility. It should be appreciated that in view of the fact that the network cloud 15 may not be dedicated to the remote mirroring data facility and may be shared with other applications 17, the performance of the system may not be as great as if a dedicated line were used to implement the link 13 (Fig. 1). However, for some user configurations, the cost savings will more than compensate for any decrease in performance.

In another illustrative embodiment of the invention, the network cloud 15 is implemented via an intranet or private enterprise network. It should be appreciated that an intranet is similar in some respects to the Internet in that a number of different users and applications typically share the resource, but the network is exclusively reserved for a private enterprise. In addition, an intranet may have one or more gateways enabling access to the Internet. An intranet is typically implemented through a public communications network (e.g., using leased lines such as a T3 line), although an intranet can alternatively be implemented using dedicated private lines. The use of an intranet as the network cloud 15 that implements the link 13 (Fig. 1) between the source and target storage systems allows an enterprise to implement a remote mirroring storage facility in an inexpensive manner using an existing enterprise network, requiring little or no changes to the network configuration, and allowing the enterprise to locate remote mirroring data facility sites based on the geography of its private network. Thus, the intranet network cloud 15 can be used to move data between various geographic locations of the enterprise to perform various applications (e.g., payroll processing), while also being used to transfer information between two or more remote mirroring data facilities.

In another embodiment of the invention, the network cloud need not be shared with any resources, and can be dedicated solely to implementing the link 13 (Fig. 1) for the remote mirroring data facility. It should be appreciated that for some user installations, a pre-existing network cloud may exist that is no longer used for other applications. As with the use of the Internet or an intranet shared with other resources, the use of a pre-existing network cloud dedicated to the remote mirroring data facility provides a convenient and cost effective way of implementing the link 13 (Fig. 1).

As shown in Fig. 2, the remote mirroring data facility can include some additional hardware to interface both the source and target storage systems to the network cloud 15. In particular, on each side of the illustrative remote mirroring data facility shown in Fig. 2 is provided a network remote data facility (RDF) controller 19 and one or more network interface units 21. In one embodiment of the invention, this additional hardware is designed to be essentially transparent to the system disclosed the assignee's above-referenced co-pending applications. As discussed above, the latency of the information transferred through the network cloud may be greater than when using a dedicated link as discussed in the co-pending applications. Thus, timeouts for awaiting the handshaking signals in the protocols of the co-pending applications can be increased to reflect the expected greater latency. No other significant changes need be made to the system disclosed in the co-pending applications.

As discussed in the co-pending applications, the source and target storage controllers 5 and 7 perform the function of implementing the protocol for transferring information between them. In one illustrative embodiment of the present invention, any of the protocols discussed in the co-pending applications can be employed. However, it should be appreciated that the present invention is not limited in this respect, and that various other protocols can be employed for transferring information between the source and target storage controllers through the network cloud 15. As discussed in the assignee's co-pending applications, the protocol for transferring information between the source and target storage systems can be implemented via a processor in each of the source and target storage controllers that is programmed by software to generate and respond to the handshaking signals that implement the protocol. Alternatively, dedicated hardware can be employed to implement this protocol.

The purpose of the network RDF controller 19 is to place the information that implements the RDF protocol into a format that is capable of transmission through the network cloud, and to control the transport of the information through the cloud. These functions can be performed in any number of ways, as discussed in more detail below. In one embodiment of the present invention, the network RDF controller 19 is implemented as a standard IBM compatible personal computer (PC) that can be programmed to perform the desired functions. Implementing the network RDF controller 19 as a PC is advantageous because such commodity based hardware is relatively inexpensive. However, it should be understood that the invention is not limited in this respect, and that a number of other types of processors can alternatively be used. Furthermore, although a programmed processor provides a simple and straightforward implementation, it should be understood that the RDF controller can also be implemented using dedicated hardware.

The network interface unit 21 provides a direct or indirect connection to the network cloud 15, and can be implemented in any of a number of different ways. The hardware to implement the network interface unit can be obtained from a network service provider, or can be purchased from a networking equipment supplier. Thus, the network interface unit can, like the network RDF controller, be implemented using commodity based equipment in a cost effective fashion. Those of ordinary skill in the art will appreciate that a number of different direct physical connections to the network cloud 15 are possible, including, but not limited to, Ethernet, Fast Ethernet, Gigabit Ethernet, fibre channel, asynchronous transfer mode (ATM) and FDDI connections. In addition, a number of indirect connections are also possible through an Internet or network service provider. The particular hardware employed will depend upon the service provider. Typical options include standard PC modems, network adapters, ADSL, cable modems and asynchronous modems. Again, the present invention is not limited to any particular type of connection to the network cloud, as numerous options are currently possible, and as it is expected that additional options will continue to become available.

The network RDF controller 19 can include a host bus adapter (not shown) that enables communication with the network interface units 21. The particular nature of the host bus adapter will depend upon the type of network interface unit 21 used to interface the network RDF controller 19 to the network cloud 15. When the network RDF controller is implemented as a PC, the host bus adapter can be implemented as a card that plugs into an internal PC bus (e.g., a standard PCI bus)

and is specifically adapted to communicate with the type of physical connection implemented by the network interface unit 21.

In one embodiment of the present invention, each of the network RDF controllers 19 can be coupled to the network cloud 15 through a single port or network interface unit 21. However, in an alternate embodiment of the invention shown in Fig. 2, multiple connections are provided to the network cloud to achieve increased performance. It should be appreciated that each path through the network cloud 15 between a pair of the network interface units 21 may be relatively slow.

Therefore, by distributing the data to be transferred over the network cloud 15 amongst a plurality of network interface units 21, the network RDF controller 19 can achieve improved performance by sending packets of information in parallel through the network cloud 15, thereby creating a larger virtual pipe through the network cloud by combining a plurality of smaller physical pipes to the network cloud. Since each of the connections provided by the network interface units 21 to the network cloud 15 is relatively inexpensive, a relatively large number of connections (e.g., fifty) may still be cost effective for a user, while providing satisfactory performance in the transmission of packets of information over the network cloud 15.

It should be appreciated that in addition to distributing the data sent from the network RDF controller 19 to the network interface units 21 as shown in Fig. 2, load sharing can also be performed at a number of other levels. For example, as shown in Fig. 4, multiple network RDF controllers can be provided, including a network RDF controller 19a coupled to the source storage controller 5 and a plurality of second level network RDF controllers 19b, each coupled to a corresponding network interface unit 21. In this implementation, data is initially distributed within the first level network RDF controller 19a, and then is further distributed in each of the second level network RDF controllers 19b. Although Fig. 4 illustrates a cascading of the network RDF controllers on only the source side of the network cloud 15, it should be appreciated that such cascading can also be performed on the target side.

In addition, data distribution can also be performed in the source storage controller 5, such that the source storage controller can be coupled to two or more network RDF controllers.

Performance is maximized in connection with the multiple paths into the network cloud by balancing the load passed between the various network interface units 21. Load balancing can be achieved using conventional techniques, such as dynamic buffer management. Similarly, the

distribution of the data can be performed using conventional techniques, such as a one-to-many queue that incorporates heuristics for circuit metering. The re-combination of the data also can be accomplished using conventional techniques, such as a many-to-one queuing mechanism with order being preserved by the tag information included with each individual packet in accordance with the

Internet Protocol discussed below.

A schematic representation of a number of software and hardware levels that can be employed to implement the illustrative embodiment of the invention shown in Fig. 2 is provided in Fig. 3. Fig. 3 illustrates a seven layer model in accordance with the Open Systems Interconnection (OSI) Reference Model developed by the International Standards Organization (ISO).

At the top level 30 is the application, which in this example is a protocol that implements the transfer of information between the source and target storage controllers 5, 7 to implement the remote data facility (RDF). As discussed above, this can be any of the protocols disclosed in the assignee's co-pending applications.

The next layer 31 is the presentation layer, which defines the format of the data transferred by the application. In one illustrative embodiment of the invention, no distinct presentation layer is provided, and the format of the data is defined in the application layer 30.

The next layer 32 is the session layer, which implements protocols for manipulating the application data prior to transportation through the network cloud. Various embodiments of the present invention support features that can be implemented in the session layer. For example, the control for the distribution of the data through multiple pipes (i.e., network interface units) into the network cloud can be implemented in the session layer. A number of proprietary systems have been developed for implementing the distribution of data through multiple pipes into a network cloud, such as the Internet or an intranet, for different types of applications, but no standard has been adopted. The present invention is not limited to any particular implementation.

Various other techniques for manipulating the application data can also be implemented in the session layer, including encryption and compression techniques discussed below.

Next is the transport layer 33 for moving packets of information over the network cloud. It should be appreciated that when packets of information are sent from a source to a destination through a network cloud 15, the packets may not arrive in the same order at the destination, and some packets may become lost. The transport protocol splits the data into multiple packets at the

source (e.g., the source storage controller 5), tags those packets to indicate the destination, then acknowledges receipt of each of the packets at the destination and reconstructs the packets in the proper order. In addition, if any packets are lost, the transport protocol can recover the lost packets and/or request that the source re-send the packets. Thus, the transport protocol provides an end-to-end reliable link between the RDF controllers 19 via the network cloud. Examples of conventional transport protocols that can be employed with the RDF application of the present invention include the User Datagram Protocol (UDP) which is a connectionless protocol, and the Transmission Control Protocol (TCP) which is a connection-oriented protocol. However, it should be appreciated that the present invention is not limited to the use of any particular transport protocol as others are possible. The transport protocol can be implemented in the network RDF controller 19, e.g., by software running on the PC when the RDF controller is implemented by a PC.

Next is the network layer 34 that builds packets of information to be passed over the cloud 15. An illustrative example for the network layer is the Internet Protocol (IP), which is the protocol that is used in passing information over the Internet. In accordance with the Internet Protocol, information is passed across the Internet in packets, each with an address identifying the destination of the packet. The generation of the packets and implementation of the Internet Protocol can be performed, like the transport layer, in the network RDF controller 19.

Next is the data link layer 35 that defines the physical format of the data to be transferred to and/or from the network cloud. As discussed above, any number of alternatives can be employed (e.g., Ethernet, T3, FDDI and ATM), with the present invention not being limited to any particular type of physical connection.

Finally, the lowest level of communication is the physical layer 36 that is the actual physical link used to interface the network RDF controller 19 to the network cloud. As discussed above, any number of alternatives can be employed (e.g., coaxial cables, fiber optic cables, copper cables, etc.), with the present invention not being limited to any particular type of physical connection.

As discussed above, conventional remote mirroring data facilities have employed either a dedicated ESCON link or a dedicated leased line to implement the link 13 (Fig. 1). Thus, conventional remote mirroring data facilities have employed a circuit switched connection, wherein all information transferred between the source and target storage controllers passes over the same path through the connection. In contrast, it should be appreciated that one aspect of the present

invention is directed to the implementation of the link 13 (Fig. 1) in a remote mirroring data facility using a packet switched or cell switched network, wherein information can be passed between the source and target storage systems through different paths through the network. As will be appreciated by those of ordinary skill in the art, packet switched networks can pass information between two points on the network through a plurality of different paths, with the information being split into multiple packets at the source, and then being reconstructed in the proper order at the destination. Cell switched networks (e.g., ATM networks) work in a similar fashion, except that information is split and distributed on cell boundaries, rather than packet boundaries. Typically, packet switched networks employ variably sized packets, whereas cell switched networks utilize cells of information having a fixed size.

It should be appreciated that by implementing the link 13 (Fig. 1) between the source and target storage systems in the remote mirroring data facility via a network cloud, a number of features commonly supported in such networks can be employed. One of these features is a multi-cast feature wherein data transferred from a source can be transmitted to more than one destination. Another related feature is a broadcast wherein data transferred from one site is transmitted to all sites. Using either of these features, a remote mirroring data facility can be employed having two target mirroring storage controllers 7 and storage devices 9 disposed at different physical locations to provide added protection for the data in the source storage system. In contrast to conventional systems wherein a dedicated or leased line must be provided between the source and each target, making the implementation of multiple mirrors very costly, the use of a pre-existing network cloud to implement the link 13 (Fig. 1) enables multiple mirrors to be provided without significant additional costs.

It should be appreciated that some network clouds employ wireless links, including satellite links or land-based links such as a point-to-point microwave communication system. Another aspect of the present invention is the recognition that such wireless communication techniques can be used to implement the link 13 in the remote mirroring data facility of Fig. 1. This aspect of the present invention is independent of the use of a network cloud, such that a dedicated wireless transmission link can be employed to implement link 13 (Fig. 1). The wireless transmission link can be implemented using any type of wireless technology (e.g., satellites and point-to-point microwave transmission), and can be implemented as a private system or can be leased from a service provider.

An illustrative implementation of the embodiment of the present invention that employs a wireless communication system to implement the link 13 (Fig. 1) between the source and target storage devices is shown in Fig. 5. As seen in Fig. 5, the network RDF controller 19 on both the source and target sides is coupled to a wireless transmitter/receiver 31. The wireless

5 transmitter/receivers communicate via a wireless communication channel 33, indicated in Fig. 5 by a dotted line. As discussed above, the wireless transmitter/receivers can be implemented using satellite technology, microwave point-to-point technology, or any other type of wireless communication technology.

In one embodiment of the present invention wherein the RDF controller 19 is implemented
10 by a PC, the PC can also execute a number of other functions for the host CPU 1 and its associated source storage system. In addition, at least one additional PC may also be provided that is on standby, and does not have any responsibilities during normal operation. In the event that a malfunction occurs with the main PC that implements the RDF controller 19, the standby PC can be used in its place, thereby increasing the reliability of the system.

15 In one embodiment of the present invention, encryption techniques are employed to provide security for the data transferred between the source and target storage units over the network cloud 15. The encryption can be performed in any number of ways, and the present invention is not limited to any particular encryption technique. For example, encryption can be performed in software in the RDF controller 19, or dedicated hardware can be used.

20 In another embodiment of the present invention, compression techniques can be employed on the data transferred between the source and target storage systems over the network cloud 15. By compressing the data prior to transmission over the network cloud 15, fewer packets of information will be sent over the network cloud, thereby increasing the performance of the system. Compression can be performed using any number of techniques, and the present invention is not limited to any
25 particular compression technique. For example, compression can be performed in software in the RDF controller 19, or dedicated hardware can be provided to implement the compression techniques.

As discussed above, the purpose for most remote mirroring data facilities is to allow for the recovery of data if a problem is experienced with the source storage system. To this end, when the
30 host CPU 1 performs a write to the source storage system, the operation will generally not terminate

until the host CPU is assured that the data has been successfully stored in the source storage system. In addition, conventional remote mirroring data facilities may also not release the host CPU 1 until an indication is provided that the data has also been successfully stored on the target storage system. However, some conventional remote mirroring data facilities have the capability of implementing a store and forward option, wherein the data written to the source storage system is also stored in a temporary storage area on the source side of the link 13 (Fig. 1), and is then subsequently transferred from the temporary storage location to the target storage system. In accordance with the store and forward option, the host CPU 1 is released when the data is stored on the source storage system and in the temporary storage area.

10 In one illustrated embodiment of the invention, the remote mirroring data facility supports the store and forward option so that, if desired by the user, the operation of the host CPU 1 is not impacted by the latency through the network cloud 15 (Fig. 2). Of course, it should be appreciated that the greatest protection for the data results when it is ultimately stored on the target storage system. Therefore, for each user application, the decision can be made as to whether to maximize
15 the protection of the system, at the expense of not releasing the host CPU 1 until the data is stored on the target storage system, or to maximize performance at the expense of some degree of data protection by releasing the host CPU 1 when the data is stored in the temporary storage area on the source side of the network cloud 15.

20 Having described several embodiments of the invention in detail, various modifications and improvements will readily occur to those skilled in the art. Such modifications and improvements are intended to be within the spirit and scope of the invention. Accordingly, the foregoing description is by way of example only, and is not intended as limiting. The invention is limited only as defined by the following claims and the equivalents thereto.

What is claimed is:

CLAIMS

1. A computer system comprising:

a central processing unit (CPU);

5 a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system;

a second storage system;

at least one communication link coupling the second storage system to the CPU, the at least one communication link including a network cloud that is shared with at least one other resource so
10 that no portion of the network cloud is dedicated exclusively to transferring information between the CPU and the second storage system; and

a mirroring controller to mirror at least some of the information stored in the first storage system in the second storage system by transferring the at least some of the information through the network cloud.

15 2. The computer system of claim 1, wherein the network cloud includes the Internet, so that the network cloud is publicly accessible.

3. The computer system of claim 1, wherein the network cloud comprises an intranet.

20 4. The computer system of claim 1, wherein the at least one communication link is one of a packet switched network and a cell switched network.

5. The computer system of claim 1, wherein the CPU includes means for communicating with
25 the at least one other resource via the network cloud.

6. The computer system of claim 1, wherein the at least one communication link includes a plurality of communication paths from the CPU to the network cloud, so that a plurality of packets of information can be transferred from the CPU to the second storage system in parallel through the
30 network cloud.

wherein the mirroring controller includes means, distributed between the first, second and third storage systems, for mirroring the at least some of the information stored in the first storage system in both of the second and third storage systems.

5 14. The computer system of claim 11, wherein the at least one communication link includes at least one wireless connection.

15. The computer system of claim 11, wherein the at least one communication link includes a plurality of communication paths from the CPU to the network cloud, so that a plurality of packets
10 of information can be transferred from the CPU to the second storage system in parallel through the network cloud.

16. The computer system of claim 15, wherein the at least one communication link includes a plurality of communication paths from the network cloud to the second storage system, so that a
15 plurality of packets of information can be transferred in parallel from the network cloud to the second storage system.

17. The computer system of claim 11, wherein the at least one communication link is one of a packet switched network and a cell switched network.

20

18. The computer system of claim 11, wherein the network cloud comprises an intranet.

19. The computer system of claim 11, wherein the network cloud includes the Internet, so that the network cloud is publicly accessible.

25

20. The computer system of claim 2, wherein the at least one communication link includes a plurality of communication paths from the network cloud to the second storage system, so that a plurality of packets of information can be transferred in parallel from the network cloud to the second storage system.

30

21. The computer system of claim 3, wherein the at least one communication link includes a plurality of communication paths from the network cloud to the second storage system, so that a plurality of packets of information can be transferred in parallel from the network cloud to the second storage system.

22. A computer system comprising:

a central processing unit (CPU);

a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system;

a second storage system;

at least one communication link coupling the second storage system to the CPU, the at least one communication link including at least one wireless connection; and

a mirroring controller to mirror at least some of the information stored in the first storage system in the second storage system by transferring the at least some of the information over the at least one communication link.

23. The computer system of claim 22, wherein the at least one communication link includes a network cloud that comprises an intranet shared by at least one other resource.

24. The computer system of claim 22, wherein the at least one communication link extends between the first and second storage systems so that the second storage system is coupled to the CPU via the first storage system.

25. The computer system of claim 24, wherein the mirroring controller includes means, distributed between the first and second storage systems, for mirroring the at least some of the information stored in the first storage system in the second storage system.

26. The computer system of claim 25, wherein the CPU is a first CPU, and wherein the system further includes a second CPU coupled to the second storage system.

27. The computer system of claim 25, wherein the at least one wireless connection is formed via a satellite communication system.

28. The computer system of claim 25, wherein the at least one wireless connection is formed via a microwave communication system.

29. The computer system of claim 22, wherein the at least one wireless connection is formed via a satellite communication system.

30. The computer system of claim 22, wherein the at least one wireless connection is formed via a microwave communication system.

31. A computer system comprising:
a central processing unit (CPU);
a first storage system;
a first communication link coupling the first storage system to the CPU so that the CPU can store information in the first storage system;
a second storage system;
a second communication link coupling the second storage system to the CPU;
a third storage system;
a third communication link coupling the third storage system to the CPU; and
a mirroring controller to mirror at least some of the information stored by the CPU in the first storage system in both the second and third storage systems.

32. The computer system of claim 31, wherein the mirroring controller is distributed between the first, second and third storage systems.

33. The computer system of claim 31, wherein the second and third communication links each comprises a network cloud that is shared by the first, second and third storage systems.

34. The computer system of claim 31, wherein at least one of the second and third communication links is one of a packet switched network and a cell switched network.

35. The computer system of claim 31, further including means for multicasting the at least some
5 of the information stored by the CPU in the first storage device to the second and third storage systems.

36. The computer system of claim 31, wherein the second communication link extends between the first and second storage systems so that the second storage system is coupled to the CPU via the
10 first storage system; and

wherein the third communication link extends between the first and third storage systems so that the third storage system is coupled to the CPU via the first storage system.

37. A method of operating a computer system that includes a central processing unit (CPU), a
15 first storage system, a first communication link coupling the first storage system to the CPU so that the CPU can store information in the first storage system, a second storage system, a second communication link coupling the second storage system to the CPU, a third storage system, and a third communication link coupling the third storage system to the CPU, the method comprising a step of:

20 (A) mirroring at least some of the information stored by the CPU in the first storage system in both the second and third storage systems by transferring the at least some of the information over the second and third communication links.

38. The method of claim 37, wherein step (A) includes steps of:

25 forming each of the second and third communication links through a network cloud that is shared by the first, second and third storage systems; and

multicasting the at least some of the information stored by the CPU in the first storage device to the second and third storage systems over the network cloud.

30 39. A method of mirroring information stored in a computer system comprising a central

processing unit (CPU), a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system, and a second storage system coupled to the CPU by at least one communication link, the at least one communication link including a network cloud that is shared with at least one other resource so that no portion of the network cloud is dedicated

5 exclusively to coupling the second storage system to the CPU, the method comprising a step of:

(A) transmitting at least some of the information stored by the CPU in the first storage system into the network cloud with the second storage system designated as a destination for the at least some of the information, so that the at least some of the information can be transferred through the network cloud and mirrored in the second storage system.

10

40. The method of claim 39, wherein the network cloud includes the Internet, and wherein step (A) includes a step of transmitting the at least some of the information into the Internet.

41. The method of claim 39, wherein the network cloud includes an intranet, and wherein step
15 (A) includes a step of transmitting the at least some of the information into the intranet.

42. The method of claim 39, wherein the CPU is coupled to the network cloud through a plurality of communication paths; and

wherein step (A) includes a step of transmitting a plurality of packets of the at least some of
20 the information in parallel from the CPU to the network cloud.

43. The method of claim 42, wherein the second storage system is coupled to the network cloud through a plurality of communication paths; and

wherein step (A) includes a step of transferring a plurality of packets of the at least some of
25 the information in parallel from the network cloud to the second storage system.

44. The method of claim 39, wherein the second storage system is coupled to the network cloud through a plurality of communication paths; and

wherein step (A) includes a step of transferring a plurality of packets of the at least some of
30 the information in parallel from the network cloud to the second storage system.

45. The method of claim 39, wherein the computer system further includes a third storage system coupled to the CPU through the network cloud, and wherein the method further comprises a step of transmitting at least some of the information stored by the CPU in the first storage system into the network cloud with the third storage system designated as a destination for the at least some of the information, so that the at least some of the information can be transferred through the network cloud and mirrored in both the second and third storage systems.

46. The method of claim 39, further comprising a step of:

(B) storing the at least some of the information transferred through the network cloud in the second storage system.

47. A computer system capable of mirroring information in a remotely disposed target storage system that is coupled to the computer system via at least one communication link that includes a network cloud that is shared with at least one other resource, the computer system comprising:

a central processing unit (CPU) coupled to the network cloud;

a source storage system that is coupled to the CPU so that the CPU can store information in the source storage system; and

a controller to transfer at least some of the information stored in the source storage system into the network cloud so that the at least some of the information can be mirrored in the target

storage system.

48. The computer system of claim 47, wherein the network cloud includes the Internet, so that the network cloud is publicly accessible.

49. The computer system of claim 47, wherein the network cloud comprises an intranet.

50. The computer system of claim 47, wherein the CPU is coupled to the network cloud through a plurality of communication paths so that a plurality of packets of information can be transferred from the CPU to the target storage system in parallel through the network cloud.

51. The computer system of claim 47, wherein the at least one communication link extends between the source and target storage systems such that the CPU is coupled to the network cloud via the source storage system.

5 52. The computer system of claim 51, wherein the controller includes means, distributed between the source and target storage systems, for mirroring the at least some of the information stored in the source storage system in the target storage system.

53. A computer system capable of mirroring information in a remotely disposed target storage
10 system that is coupled to the computer system via at least one communication link that includes at least one wireless connection, the computer system comprising:

a central processing unit (CPU) coupled to the at least one communication link;

a source storage system that is coupled to the CPU so that the CPU can store information in the source storage system; and

15 a controller to transfer at least some of the information stored in the source storage system into the network cloud so that the at least some of the information can be mirrored in the target storage system.

54. The computer system of claim 53, wherein the at least one wireless connection is formed via
20 a satellite communication system.

55. The computer system of claim 53, wherein the at least one wireless connection is formed via a microwave communication system.

25 56. A computer system comprising:

a central processing unit (CPU);

a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system;

a second storage system;

30 at least one communication link coupling the second storage system to the CPU so that the

CPU can store information in the second storage system, the at least one communication link being selected from one of an Ethernet link, an asynchronous transfer mode (ATM) link, an FDDI link and a fibre channel link; and

a mirroring controller to mirror at least some of the information stored in the first storage system in the second storage system by transferring the at least some of the information over the at least one communication link.

57. The computer system of claim 56, wherein the at least one communication link extends between the first and second storage systems such that the second storage system is coupled to the CPU via the first storage system.

58. The computer system of claim 57, wherein the mirroring controller includes means, distributed between the first and second storage systems, for mirroring the at least some of the information stored in the first storage system in the second storage system.

59. A computer system comprising:

a central processing unit (CPU);

a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system;

a second storage system;

at least one communication link coupling the second storage system to the CPU so that the CPU can store information in the second storage system, the at least one communication link being one of a packet switched network and a cell switched network; and

a mirroring controller to mirror at least some of the information stored in the first storage system in the second storage system by transferring the at least some of the information over the at least one communication link.

60. The computer system of claim 59, wherein the at least one communication link extends between the first and second storage systems such that the second storage system is coupled to the CPU via the first storage system.

61. A computer system comprising:

a central processing unit (CPU);

a first storage system that is coupled to the CPU so that the CPU can store information in the first storage system;

5 a second storage system;

at least one communication link coupling the second storage system to the CPU so that the CPU can store information in the second storage system, the at least one communication link including a network cloud; and

a mirroring controller to mirror at least some of the information stored in the first storage system in the second storage system by transferring the at least some of the information over the network cloud.

10

SECRET




Fig. 1

(Prior Art)




Fig. 2

Application Layer (e.g., RDF Protocol)	~ 30
Presentation Layer	~ 31
Session Layer	~ 32
Transport Layer (e.g., UDP, TCP)	~ 33
Network Layer (e.g., IP)	~ 34
Data Link Layer (e.g., Ethernet, T3, ATM)	~ 35
Physical Layer	~ 36

Fig. 3




Fig. 4




Fig. 5

DECLARATION FOR PATENT APPLICATION

As a below named inventor, we hereby declare that:

Our residence, post office address and citizenship are as stated below next to our names.

We believe we are an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled

A METHOD AND APPARATUS FOR IMPLEMENTING A REMOTE MIRRORING DATA FACILITY

the specification of which is attached hereto unless the following is checked:

☐ was filed on _____, as United States Application No. _____ or PCT
(Include Series Code)
International Application No. _____, bearing attorney docket No.
_____, and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or section 365(a) of any PCT International application designating at least one country other than the United States listed below and have also identified below any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed:

Prior Foreign PCT International Application(s) and any priority claims under 35 U.S.C. §§119 and 365(a), (b):

(Number)	(Country-if PCT, so indicate)	(DD/MM/YY Filed)	Priority Claimed <input type="checkbox"/> <input type="checkbox"/>
			YES NO
(Number)	(Country)	(DD/MM/YY Filed)	<input type="checkbox"/> <input type="checkbox"/>
			YES NO
(Number)	(Country)	(DD/MM/YY Filed)	<input type="checkbox"/> <input type="checkbox"/>
			YES NO

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below:

_____ (Application Number)	_____ (filing date)
_____ (Application Number)	_____ (filing date)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s), or §365(c) of any PCT International application(s) designating the United States of America listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56

which became available between the filing date of the prior application and the national or PCT International filing date of this application:

(Application No.)	(filing date)	(status-patented, pending, abandoned)
-------------------	---------------	---------------------------------------

PCT International Applications designating the United States:

(PCT Appl. No.)	(U.S. Ser. No.)	(PCT filing date)	(status-patented, pending, abandoned)
-----------------	-----------------	-------------------	---------------------------------------


1. I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

David Wolf	17,528	Peter C. Lando	34,654	Douglas C. Doskocil	39,660
George L. Greenfield	17,756	Gary S. Engelson	35,128	John R. Van Amsterdam	40,212
Stanley Sacks	19,900	Peter J. Gordon	35,164	Scott A. Ouellette	38,573
Edward F. Perlman	28,105	Randy J. Pritzker	35,986	Matthew B. Lowrie	38,228
Lawrence M. Green	29,384	Richard F. Guinta	36,149	Jodi-Ann McLane	36,215
Steven J. Henry	27,900	Douglas R. Wolf	36,971	Michael G. Verga	39,410
Therese A. Hendricks	30,389	Elizabeth R. Plumer	36,637	Robert E. Rigby, Jr.	36,904
Edward R. Gates	31,616	Timothy J. Oyer	36,628	Sean P. Daley	40,978
William R. McClellan	29,409	Kristofer E. Elbing	34,590	Robert A. Skrivanek, Jr.	41,316
Ronald J. Kransdorf	20,004	John N. Anastasi	37,765	Robert M. Abrahamsen	40,886
M. Lawrence Oliverio	30,915	Brett N. Dorny	35,860	Lesley A. Hamlin	41,054
James J. Foster	30,052	Helen C. Kindregan	39,248	Lindsay G. McGuinness	38,549
Charles E. Pfund	17,030	James M. Hanifin, Jr.	39,213	Mike W. Crosby	40,970
Anthony J. Mirabito	28,161	Thomas M. Sullivan	39,392	Ivan D. Zitkovsky	37,482
Jason M. Honeyman	31,624	Christopher S. Schultz	37,929		
James H. Morris	34,681	Paul D. Sorkin	39,039		

Address all telephone calls to Richard F. Giunta at telephone no. (617) 720-3500. Address all correspondence to

Richard F. Giunta
c/o Wolf, Greenfield & Sacks, P.C.,
Federal Reserve Plaza
600 Atlantic Avenue
Boston, MA 02210-2211

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.


Inventor's signature
Full name of sole or first inventor Robert Wilson
Citizenship U.S.
Residence 8 Ledgestone Drive, Hopkinton, MA 01748
Post Office Address 8 Ledgestone Drive, Hopkinton, MA 01748

8/22/87
Date



9/22/97

Inventor's signature
Full name of second or joint inventor Dennis P.J. Ting
Citizenship Canada
Residence 31 Acorn Path, Groton, MA 01450
Post Office Address 31 Acorn Path, Groton, MA 01450

Date



9/22/97

Inventor's signature
Full name of third or joint inventor Mehamood Hosein
Citizenship U.S.
Residence 29 William Kelley Road, Stoughton, MA 02072
Post Office Address 29 William Kelley Road, Stoughton, MA 02072

Date

45260-443600